


AGRIMAX V- FLECTO

TIRE SIZE	VF 540/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	162 D



РАЗМЕРЫ IS STANDARD

SW (MM)	549	RIM REC	DW 20 B
OD (MM)	1676	RIM ALT	DW 18 L
SLR (MM)	760	ECE	E11-106R-005020
RC (MM)	4981	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2200	2545	2890	3285	3585	3890	4320
FROM 65 TO 40	2420	2800	3180	3610	3940	4275	4750
30	2465	2855	3240	3680	4015	4360	4845
20	5215	2910	3305	3750	4095	4445	4940
10	2660	3080	3495	3970	4330	4700	5225
*UPTO 10 CYC WITH FRONT LOADER	3385	3920	4450	5050	5515	5985	6650
10HT	2465	2855	3240	3680	4015	4360	4845

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.