


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	185 D



РАЗМЕРЫ US STANDARD

USA CODE	94075812	RC (IN)	243.4
SW (IN)	28.1	RIM REC	DW 25 B
OD (IN)	81.1	RIM ALT	DW 23 B; DW 24 B
SLR (IN)	35.8	ECE	E11-106R-006266

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8730	10020	11510	13000	14470	15960	17450	18550
FROM 40 TO 25	9590	11010	12640	14270	15910	17540	19170	20390
20	9780	11230	12900	14560	16230	17890	19550	20800
12	9980	11450	13150	14850	16540	18240	19940	21210
5	10550	12110	13910	15710	17500	19300	21090	22430
UPTO 20 CYC	10880	12500	14350	16200	18050	19910	21760	23140
UPTO 10 CYC	12980	14920	17130	19340	21550	23760	25970	27620
UPTO 5CYC	14240	16360	18780	21200	23620	26050	28470	30280
5 HT	9780	11230	12900	14560	16230	17890	19550	20800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.