


# TR 461

<b>TIRE SIZE</b>	<b>15.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	CHARGEUSE TÉLESCOPIQUE / CHARGEUSE-PELLETEUSE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8
<b>LI/SS FREE ROLLING</b>	150 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94067428	<b>RC (IN)</b>	114.3
<b>SW (IN)</b>	12.0	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	38.9	<b>RIM ALT</b>	11
<b>SLR (IN)</b>	17.1	<b>ECE</b>	E11-106R-006914

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	80
5 FR	10340
15 FR	8780
20 FR	8270
25 FR	7390
5 DW	7290
15 DW	6190
20 DW	5830
25 DW	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.