

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	174 A8/170 B
<b>LI/SS FREE ROLLING</b>	186 A8/182 B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	850	<b>RIM REC</b>	AG 28.00
<b>OD (MM)</b>	1650	<b>ECE</b>	E11-106R-004565
<b>SLR (MM)</b>	710	<b>PR</b>	16
<b>RC (MM)</b>	4935		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	11830	12580	13300
20 FR	10645	11320	11970
30 FR	9465	10065	10640
40 FR	8450	8985	9500
50 FR	7605	8085	8500
10 DW	8345	8870	9380
20 DW	7510	7980	8440
30 DW	6675	7095	7505
40 DW	5960	6335	6700
50 DW	5365	5700	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.