


# AT 171

<b>TIRE SIZE</b>	<b>38X10 - 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	VEÍCULO ATV / VEICULO PARA LAS CORRIDAS DE LAMA / TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	93 A8 ; 69 F



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94055180	<b>RC (IN)</b>	111.6
<b>SW (IN)</b>	9.3	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	37.4	<b>RIM ALT</b>	W 7
<b>SLR (IN)</b>	17.4	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>20</b>	<b>15</b>
<b>25 MUD BOGGING</b>	1433	-
<b>50 MUD BOGGING</b>	715	-
<b>25 CASUAL TRANSPORT</b>	-	1170
<b>50 CASUL TRANSPORT</b>	-	585

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.