

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>210/95 R 16</b>                                                    |
| <b>UM</b>        | IS STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 106 A8/B                                                              |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 214  | <b>RIM REC</b> | W 7            |
| <b>OD (MM)</b>  | 806  | <b>RIM ALT</b> | W 6 ; 6 LB     |
| <b>SLR (MM)</b> | 360  | <b>ECE</b>     | E4-106R-000608 |
| <b>RC (MM)</b>  | 2387 | <b>SRI</b>     | 370            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6  | 2.0  | 2.4  |
|--------------|-----|-----|-----|-----|-----|------|------|------|
| <b>50</b>    | 450 | 515 | 590 | 665 | 745 | 820  | 885  | 950  |
| <b>40</b>    | 450 | 515 | 590 | 665 | 745 | 820  | 885  | 950  |
| <b>30</b>    | 480 | 555 | 635 | 715 | 800 | 880  | 950  | 1020 |
| <b>10 LT</b> | 600 | 690 | 795 | 895 | 995 | 1100 | 1190 | 1275 |
| <b>10 HT</b> | 480 | 555 | 635 | 715 | 800 | 880  | 950  | 1020 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.