DATA SHEET

PRINTED ON
21-04-2026

POWER TRAX

TIRE SIZE	**355/65 - 15**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	EMPTY CONTAINER HANDLER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 A5

DIMENSIONS IS STANDARD

SW (MM)	335	**RIM REC**	9.75
OD (MM)	830	**PR**	24
SLR (MM)	380		
RC (MM)	2530		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	10.00
25 LOAD WHEEL	7800
25 STEER WHEEL	6000
10 OTHER VEHICLES	7800
25 OTHER VEHICLES	6000
STATIC SIDE LOADER	9060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..