

# EARTHMAX SR 30

|           |                                                  |
|-----------|--------------------------------------------------|
| TIRE SIZE | 23.5 R 25                                        |
| UM        | IS STANDARD                                      |
| MACHINERY | ARTICULATED DUMP TRUCK (ADT) /<br>DOZER / LOADER |
| VERSION   | CUT RESISTANT COMPOUND                           |
| TL/TT     | TL                                               |
| LI/SS     | 185 B ; 195 A2                                   |



## DIMENSIONS IS STANDARD

|          |           |             |       |
|----------|-----------|-------------|-------|
| OD (MM)  | 1607      | TRA CODE    | E3/L3 |
| SLR (MM) | 711       | STAR RATING | ★★★   |
| RC (MM)  | 4797      |             |       |
| RIM REC  | 19.50/2.5 |             |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00  | 4.25  | 4.50  | 4.75  | 5.00  | 5.25 |
|------------|-------|-------|-------|-------|-------|------|
| 50         | 7500  | 7750  | 8250  | 8500  | 9000  | 9250 |
| 10         | 10300 | 10600 | 11200 | 11500 | 12150 | -    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.