


# BK-LOADER 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>405/70 R 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ÎNCĂRCĂTOR   |
| <b>VERSION</b>      | ARAMID BELTED  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 155A2/151A4  |



## DIMENSIUNI US STANDARD

|                 |          |                |                       |
|-----------------|----------|----------------|-----------------------|
| <b>USA CODE</b> | 94054428 | <b>RC (IN)</b> | 131.5                 |
| <b>SW (IN)</b>  | 16.0     | <b>RIM REC</b> | 13                    |
| <b>OD (IN)</b>  | 43.2     | <b>RIM ALT</b> | 14; 13 SDC; 12;12 SDC |
| <b>SLR (IN)</b> | 20.1     |                |                       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22   | 29   | 36   | 44   | 51   | 58    | 65    | 73    | 80    |
|-----------|------|------|------|------|------|-------|-------|-------|-------|
| 12        | 2670 | 3350 | 3980 | 4610 | 5240 | 5820  | 6400  | 6990  | 7610  |
| 5         | 3030 | 3800 | 4520 | 5240 | 5950 | 6610  | 7270  | 7940  | 8540  |
| STATIC    | 4850 | 6060 | 7220 | 8380 | 9530 | 10580 | 11680 | 12680 | 13670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.