

AS 504

TIRE SIZE	6.00 - 16
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	HD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	91 A8
LI/SS FREE ROLLING	103 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	164	RIM REC	4.00 E
OD (MM)	735	RIM ALT	4.50 E; 4½ K
SLR (MM)	343	ECE	E11-106R-005195
RC (MM)	2190	PR	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	1225
25 FR	1040
30 FR	980
40 FR	875
10 DW	860
25 DW	730
30 DW	690
40 DW	615

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.