

# RIB 774 (A)

<b>TIRE SIZE</b>	<b>12.0 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	150 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010844	<b>RC (IN)</b>	105.8
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	35.5	<b>ECE</b>	E11-106R-005355
<b>SLR (IN)</b>	16.3	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	75
5 FR	10340
15 FR	8780
20 FR	8270
25 FR	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.