

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 600/55 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 151 A8/ 148 B |
| LI/SS FREE ROLLING | 164 A8/160 B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 600 | RIM REC | AG 20.00 |
| OD (MM) | 1230 | ECE | E11-106R-004553 |
| SLR (MM) | 540 | PR | 12 |
| RC (MM) | 3716 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 1.70 | 2.00 |
|------------|------|------|------|
| 10 FR | 5915 | 6365 | 7000 |
| 20 FR | 5325 | 5725 | 6300 |
| 30 FR | 4730 | 5090 | 5600 |
| 40 FR | 4225 | 4545 | 5000 |
| 50 FR | 3805 | 4090 | 4500 |
| 10 DW | 4080 | 4390 | 4830 |
| 20 DW | 3675 | 3950 | 4345 |
| 30 DW | 3265 | 3510 | 3865 |
| 40 DW | 2915 | 3135 | 3450 |
| 50 DW | 2625 | 2820 | 3150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.