


# RT 747 AGRO INDUSTRIAL

<b>TIRE SIZE</b>	<b>460/70 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	465	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1254	<b>RIM ALT</b>	DW 14 L; DW 16 L
<b>SLR (MM)</b>	556	<b>ECE</b>	E11-106R-004071
<b>RC (MM)</b>	3840	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
50	1670	2060	2415	2805	3160	3550
40	1670	2060	2415	2805	3160	3550
30	1785	2205	2585	3000	3380	3800
25	1850	2285	2680	3115	3505	3940
10 CYC	2505	3090	3620	4205	4740	5325
STATIC	3505	4325	5070	5890	6635	7455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.