

# AGRIMAX RT 765M

**710/70 R 38****UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** İLAÇLAMA / TRAKTÖR / ÜZÜM HASAT  
MAKİNESİ / BIÇERDÖVER /  
UYGULAMALI MAKİNE**VERSION** STANDARD**TIRE TYPE** TL

166 D



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1959	<b>RIM ALT</b>	DW 25 B
<b>SLR (MM)</b>	859	<b>ECE</b>	E11-106R-005837
<b>RC (MM)</b>	5751	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	2915	3395	3870	4350	4825	5300
50	3065	3565	4065	4565	5065	5565
40	3195	3720	4240	4765	5285	5805
30	3355	3905	4450	5000	5550	6095
10 LT	3910	4550	5190	5830	6470	7105
10 HT	3355	3905	4450	5000	5550	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.