

# AW 708

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 520/50 - 17   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ❖ BIAS  |
| <b>MACHINERY</b>          | PRESĂ DE BALOTAT / MAȘINI DE<br>IMPLEMENTARE / REMORCĂ / MAȘINĂ<br>DE RECOLTARE / MAȘINI DE<br>IMPLEMENTARE / REMORCĂ |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 162 A8  |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063413 | <b>RC (IN)</b> | 109.3           |
| <b>SW (IN)</b>  | 20.3     | <b>RIM REC</b> | 16.00           |
| <b>OD (IN)</b>  | 37.5     | <b>ECE</b>     | E11-106R-005852 |
| <b>SLR (IN)</b> | 15.9     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>58</b> |
|------------------|-----------|
| 5 FR             | 14660     |
| 15 FR            | 12465     |
| 20 FR            | 11730     |
| 25 FR            | 10470     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.