

# LOADER PLUS

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 17.5 - 25   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | PALA CARGADORA / BULDÓCER / PALA CARGADORA / BULDÓCER |
| <b>VERSIÓN</b>      | DUAL BEAD   |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONES US STANDARD

|                   |          |                 |           |
|-------------------|----------|-----------------|-----------|
| <b>CÓDIGO USA</b> | 94064953 | <b>RIM REC</b>  | 14.00/1.5 |
| <b>OD (IN)</b>    | 53.0     | <b>PR</b>       | 20        |
| <b>SLR (IN)</b>   | 24.5     | <b>TRA CODE</b> | L3        |
| <b>RC (IN)</b>    | 156.7    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>83</b> |
| 5                | 18200     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.