

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/156 B
<b>LI/SS FREE ROLLING</b>	173 A8/169 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	600	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1230	<b>ECE</b>	E11-106R-004393
<b>SLR (MM)</b>	540	<b>PR</b>	20
<b>RC (MM)</b>	3716		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.10	3.20
10 FR	8765	8930	9100
20 FR	7890	8040	8190
30 FR	7010	7145	7280
40 FR	6260	6380	6500
50 FR	5635	5740	5800
10 DW	6070	6180	6300
20 DW	5460	5565	5670
30 DW	4855	4945	5040
40 DW	4335	4415	4500
50 DW	3900	3975	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.