


# RIDEMAX FL 693 M



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 710/45 R 22.5  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TANKBIL / SLÄPVAGN /<br>ARBETSFORDON   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 165 D  |

## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 706  | <b>RIM REC</b> | AG 24.00        |
| <b>OD (MM)</b>  | 1212 | <b>ECE</b>     | E11-106R-005994 |
| <b>SLR (MM)</b> | 542  | <b>SRI</b>     | 575             |
| <b>RC (MM)</b>  | 3658 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|
| 70         | 1715 | 1925 | 2390 | 2720 | 3140 | 3565 | 3890 | 4265 | 4685 |
| 65         | 1880 | 2115 | 2630 | 2990 | 3455 | 3915 | 4275 | 4690 | 5150 |
| 50         | 2280 | 2560 | 3180 | 3620 | 4180 | 4740 | 5180 | 5675 | 6235 |
| 40         | 2560 | 2875 | 3575 | 4065 | 4695 | 5325 | 5815 | 6375 | 7005 |
| 30         | 2840 | 3190 | 3970 | 4515 | 5215 | 5915 | 6460 | 7080 | 7780 |
| 25         | 2975 | 3340 | 4155 | 4725 | 5455 | 6190 | 6760 | 7410 | 8140 |
| 10         | 3385 | 3805 | 4730 | 5380 | 6215 | 7050 | 7695 | 8440 | 9270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.