


AGRIMAX RT 657

TIRE SIZE	540/65 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	146 D ; 149 A8



DIMENSIONS IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1312	RIM ALT	W 18 L
SLR (MM)	596	ECE	E4-106R-000773
RC (MM)	3942	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1440	1680	1890	2100	2310	2490	2760	3000
50	1515	1765	1985	2205	2430	2615	2900	3150
40	1560	1820	2050	2275	2505	2700	2990	3250
30	1660	1935	2175	2415	2660	2865	3175	3450
10 LT	1930	2255	2535	2815	3100	3340	3700	4020
10 HT	1660	1935	2175	2415	2660	2865	3175	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.