


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>580/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 D ; 161 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	577	<b>RIM REC</b>	W 18 L
<b>OD (MM)</b>	1879	<b>RIM ALT</b>	DW18L;DD18L
<b>SLR (MM)</b>	856	<b>ECE</b>	E11-106R-0010076
<b>RC (MM)</b>	5693	<b>SRI</b>	900

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
65	2340	2720	3105	3485	3870	4250
50	2460	2860	3260	3665	4065	4465
40	2545	2960	3380	3795	4210	4625
30	2690	3130	3570	4010	4450	4890
10 LT	3135	3645	4160	4670	5185	5695
10HT	2690	3130	3570	4010	4450	4890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.