DATA SHEET

Última atualização
2-06-2026

AS 504

TIRE SIZE	**10.0/75 -15.3**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

DIMENSÕES IS STANDARD

SW (MM)	264	**RIM REC**	9.00
OD (MM)	785	**ECE**	E4-106R-001823
SLR (MM)	360	**PR**	18
RC (MM)	2404	**SRI**	360

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	7.10
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..