


# EARTHMAX SR 41

<b>TIRE SIZE</b>	<b>23.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BULDOZER / ÎNCĂRCĂTOR / BASCULANTĂ ARTICULATĂ (ADT) / AUTOBASCULANTĂ CU PROFIL REDUS (LPDT)
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 B ; 195 A2



## DIMENSIUNI IS STANDARD

<b>OD (MM)</b>	1611	<b>TRA CODE</b>	E4/L4
<b>SLR (MM)</b>	725	<b>STAR RATING</b>	★★/★
<b>RC (MM)</b>	4790		
<b>RIM REC</b>	19.50/2.5		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	7500	7750	8250	8500	9000	9250
10	10300	10600	11200	11500	12150	--

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.