

# SM 55 L5S

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 17.5 - 25   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | VEICULO PARA MINAS SUBTERRÂNEAS<br>/ DUMPER DE BAIXO PERFIL |
| <b>VERSÃO</b>       | STEEL BELTED  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSÕES IS STANDARD

|                 |           |                 |                           |
|-----------------|-----------|-----------------|---------------------------|
| <b>OD (MM)</b>  | 1375      | <b>RIM ALT</b>  | 14.00/1.3; 14.00/1.4 (DC) |
| <b>SLR (MM)</b> | 631       | <b>PR</b>       | 20                        |
| <b>RC (MM)</b>  | 4043      | <b>TRA CODE</b> | L5S                       |
| <b>RIM REC</b>  | 14.00/1.5 |                 |                           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.75 |
|------------|------|
| 10         | 8250 |
| 15         | 7180 |
| 25         | 6600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.