

FLOTATION 648

TIRE SIZE	800/45 - 26.5
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	170 A8/167 B
LI/SS FREE ROLLING	183 A8/180 B



ABMESSUNGEN US STANDARD

USA-CODE	94052929	RC (IN)	164.8
SW (IN)	31.5	RIM REC	AG 28.00
OD (IN)	54.8	ECE	E11-106R-004618
SLR (IN)	24.8	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	38	39	41
5 FR	25860	26430	27010
10 FR	23280	23790	24300
20 FR	20690	21150	21600
25 FR	18470	18880	19290
30 FR	16620	17000	17640
5 DW	17740	18130	18520
10 DW	15960	16320	16670
20 DW	14190	14510	14810
25 DW	12660	12950	13230
30 DW	11400	11660	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.