

FLOTATION 558

| | |
|---------------------|--|
| | 400/55 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALYA MAKINESI / BIÇERDÖVER / TANKER / RÖMORK / BIÇERDÖVER / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 144 A8/140 B |
| | 156 A8/152 B |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|------------------------|
| SW (MM) | 405 | RIM REC | AG 11.75 |
| OD (MM) | 1020 | RIM ALT | 12.25; 13.00; AG 13.00 |
| SLR (MM) | 445 | ECE | E11-106R-005351 |
| RC (MM) | 3084 | PR | 20 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.60 | 4.80 | 5.00 |
|------------|------|------|------|
| 10 FR | 5335 | 5465 | 5600 |
| 20 FR | 4800 | 4920 | 5040 |
| 30 FR | 4265 | 4375 | 4480 |
| 40 FR | 3810 | 3905 | 4000 |
| 50 FR | 3430 | 3515 | 3550 |
| 10 DW | 3730 | 3830 | 3920 |
| 20 DW | 3360 | 3445 | 3530 |
| 30 DW | 2985 | 3065 | 3135 |
| 40 DW | 2665 | 2735 | 2800 |
| 50 DW | 2400 | 2460 | 2500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.