

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	159 A8/156 B
<b>LI/SS FREE ROLLING</b>	170 A8/167 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006441	<b>RC (IN)</b>	158.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	53.3	<b>ECE</b>	E4-106R-002276
<b>SLR (IN)</b>	22.9	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
5 FR	16790	17670	18520
10 FR	15110	15910	16670
20 FR	13440	14130	14810
25 FR	11990	12620	13230
30 FR	10790	11360	12010
5 DW	12260	12890	13500
10 DW	11020	11600	12160
20 DW	9800	10310	10800
25 DW	8750	9200	9640
30 DW	7880	8290	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.