


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 380/85 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 131 A8/B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94044672 | RC (IN) | 146.5 |
| SW (IN) | 15.0 | RIM REC | W 12 |
| OD (IN) | 49.4 | RIM ALT | W 11; W 13 |
| SLR (IN) | 21.8 | ECE | E4-106R-000592 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------|------|------|------|------|------|------|
| 30 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 25 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 20 | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |
| 5 LT | 3170 | 3690 | 4210 | 4730 | 5250 | 5760 |
| 5 HT | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.