

FLOTATION 648

TIRE SIZE	700/40 - 22.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/ 162 B



DIMENSIONS IS STANDARD

SW (MM)	700	RIM REC	AG 24.00
OD (MM)	1170	ECE	E4-106R-002311
SLR (MM)	510	PR	16
RC (MM)	3537		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	6600	7020	7420
20 FR	5940	6320	6680
30 FR	5280	5615	5935
40 FR	4715	5015	5300
50 FR	4245	4515	4750
10 DW	4670	4965	5250
20 DW	4200	4465	4725
30 DW	3735	3970	4200
40 DW	3335	3545	3750
50 DW	3000	3190	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.