

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8/151 B
<b>LI/SS FREE ROLLING</b>	167 A8/163 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94030781	<b>RC (IN)</b>	137.8
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-002275
<b>SLR (IN)</b>	20.1	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	39	41	42
<b>5 FR</b>	16130	16480	16820
<b>10 FR</b>	14520	14840	15130
<b>20 FR</b>	12900	13180	13460
<b>25 FR</b>	11520	11770	12010
<b>30 FR</b>	10370	10590	10750
<b>5 DW</b>	11460	11720	11960
<b>10 DW</b>	10320	10540	10770
<b>20 DW</b>	9170	9370	9570
<b>25 DW</b>	8190	8370	8540
<b>30 DW</b>	7370	7530	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.