



IS standard



GROWING TOGETHER

TR 270



PRODUCT DATA SHEET



Bias



TR 270



TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



For muddy ground



Self-Cleaning



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	8	TT	145 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	10	TT	149 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	12	TL	153 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	12	TT	153 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	14	TT	156 A6
Ø 30"	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	8	TL	139 A6
	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	8	TT	139 A6
	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	12	TT	149 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	8	TT	146 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	10	TT	151 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	12	TT	155 A6
Ø 34"	18.4 - 34	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	STD	8	TT	142 A6
	18.4 - 34	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	STD	12	TT	150 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	8	TT	148 A6

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



For muddy ground



Self-Cleaning



Traction



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 34"	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	10	TT	153 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	12	TT	156 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	14	TL	160 A6
Ø 38"	13.6 - 38	W12	DW 12 A ; W 11	345	1600	-	4828	STD	6	TT	122 A6
	18.4 - 38	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	STD	8	TT	143 A6
	18.4 - 38	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	STD	12	TT	153 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	8	TT	148 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	10	TT	151 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	12	TT	156 A6
Ø 46"	13.6 - 46	W 12	W 12 A	345	1804	-	5440	STD	6	TT	125 A6

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference