


# AGRIMAX V-FLECTO

TIRE SIZE	VF 580/85 R 46 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVÉRISATEUR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	179 D



## DIMENSIONS IS STANDARD

SW (MM)	605	RIM REC	DW 20 B
OD (MM)	2156	RIM ALT	DW 21 B, DW18L
SLR (MM)	947	ECE	E11-106R-0011691
RC (MM)	6451	SRI	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	3530	4095	4660	5295	5860	6425	7055
FROM 65 TO 40	3875	4495	5115	5815	6435	7055	7750
30	3955	4585	5220	5930	6565	7195	7905
20	4030	4675	5320	6045	6690	7335	8060
10	4265	4945	5630	6395	7080	7760	8525
10HT	3955	4585	5220	5930	6565	7195	7905
UPTO 10 CYC	5755	6680	7600	8635	9555	10475	11510
UPTO 15 CYC	5255	6095	6935	7880	8720	9560	10505
UPTO 30 CYC	4400	5105	5810	6600	7305	8010	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.