

AGRIMAX RT 855

TIRE SIZE	340/85 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	127 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94021611	RC (IN)	153.1
SW (IN)	13.9	RIM REC	W 12
OD (IN)	50.7	RIM ALT	W 11
SLR (IN)	23.1	ECE	E4-106R-000593

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2130	2470	2820	3160	3520	3860
25	2130	2470	2820	3160	3520	3860
20	2280	2650	3020	3390	3770	4130
5 LT	2840	3320	3780	4240	4710	5170
5 HT	2280	2650	3020	3390	3770	4130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.