DATA SHEET

PRINTED ON
23-04-2026

AS 504

TIRE SIZE	**7.50 - 18**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	SOLLEVATORE TELESCOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	122 A8

DIMENSIONI US STANDARD

CODICE USA	94065394	**RC (IN)**	104.3
SW (IN)	8.2	**RIM REC**	5.50 F
OD (IN)	33.6	**RIM ALT**	4.50 E; 6.00 F; 5.00 F
SLR (IN)	16.0	**ECE**	E11-106R-006456

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	74
5 FR	4630
15 FR	3935
20 FR	3700
25 FR	3300
5 DW	3360
15 DW	2855
20 DW	2690
25 DW	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..