

# LG 306

|                     |                                    |
|---------------------|------------------------------------|
| <b>TIRE SIZE</b>    | 20X8.00 - 10                       |
| <b>UM</b>           | US STANDARD                        |
| <b>CONSTRUCTION</b> | BIAS                               |
| <b>MACHINERY</b>    | COSITTOARE / TRACTOR MIC / TRACTOR |
| <b>VERSION</b>      | STANDARD                           |
| <b>TIRE TYPE</b>    | TL                                 |



## DIMENSIONI US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA CODE</b> | 94012732 | <b>RC (IN)</b> | 57.1                        |
| <b>SW (IN)</b>  | 8.1      | <b>RIM REC</b> | 6.00 I - 55; I - 70; I - 90 |
| <b>OD (IN)</b>  | 19.7     | <b>RIM ALT</b> | 6 JA                        |
| <b>SLR (IN)</b> | 8.8      | <b>ECE</b>     | E11-106R-003456             |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>36</b> |
| 10               | 1125      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.