


# TF 9090

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>7.50 - 18</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR / TRAILER  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 97 A8  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94021154 | <b>RC (IN)</b> | 100.9           |
| <b>SW (IN)</b>  | 8.1      | <b>RIM REC</b> | 5.50 F          |
| <b>OD (IN)</b>  | 33.9     | <b>ECE</b>     | E11-106R-004317 |
| <b>SLR (IN)</b> | 15.9     | <b>PR</b>      | 6               |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 25               | 1610      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.