

AGRIMAX TURF RT 333

TIRE SIZE	260/70 R 16
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDEMMIATRICE / MACCHINA PER IL RACCOLTO DI FRUTTETI / TRATTORINO / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	109 A8 ; 109 B



DIMENSIONI US STANDARD

CODICE USA	94067909	RC (IN)	90.0
SW (IN)	10.2	RIM REC	W 8
OD (IN)	30.3	RIM ALT	W 8 L ; W 9
SLR (IN)	13.7	ECE	E11-106R-007158

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1070	1240	1420	1600	1780	1970	2140	2280
25	1070	1240	1420	1600	1780	1970	2140	2280
20	1150	1330	1530	1710	1910	2110	2300	2440
5 LT	1450	1660	1900	2140	2400	2640	2880	3060
5 HT	1150	1330	1530	1710	1910	2110	2300	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.