

# TR 390

|                     |                                     |
|---------------------|-------------------------------------|
| <b>TIRE SIZE</b>    | <b>28L - 26</b>                     |
| <b>UM</b>           | US STANDARD                         |
| <b>CONSTRUCTION</b> |                                     |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS /<br>COMPACTOR |
| <b>VERSION</b>      | DUAL BEAD                           |
| <b>TIRE TYPE</b>    | TL                                  |
| <b>LI/SS</b>        | 157 A8                              |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94070695 | <b>RC (IN)</b> | 178.9          |
| <b>SW (IN)</b>  | 28.1     | <b>RIM REC</b> | DW 25 B        |
| <b>OD (IN)</b>  | 61.4     | <b>RIM ALT</b> | DW 23 B        |
| <b>SLR (IN)</b> | 27.2     | <b>ECE</b>     | E4-106R-002337 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>28</b> |
| 25               | 9100      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.