


EARTHMAX SR 49 M

| | |
|---------------------|--|
| TYRE SIZE | 29.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | DOZER / LOAD HAUL DUMP / LOADER |
| VERSION | CUT RESISTANT COMPOUND |
| TYRE TYPE | TL |
| LI/SS | 200 B ; 216 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1905 | TRA CODE | E4/L4 |
| SLR (MM) | 844 | STAR RATING | ★★ |
| RC (MM) | 5600 | | |
| RIM REC | 25.00/3.5 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 11500 | 11800 | 12500 | 12850 | 13600 | 14000 | - | - | - | - | - |
| 10 | - | - | - | - | - | 19000 | 19500 | 20000 | 20600 | 21200 | 22400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.