

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	OUTILLAGE AGRICOLE / REMORQUE / OUTILLAGE AGRICOLE
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8/151 B
<b>LI/SS FREE ROLLING</b>	168 A8/164 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	515	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1181	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (MM)</b>	542	<b>ECE</b>	E11-106R-004395
<b>RC (MM)</b>	3604	<b>PR</b>	20

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70	3.80	4.00
10 FR	7425	7545	7840
20 FR	6685	6790	7055
30 FR	5940	6035	6270
40 FR	5305	5390	5600
50 FR	4775	4850	5000
10 DW	5255	5340	5425
20 DW	4730	4805	4885
30 DW	4205	4275	4340
40 DW	3755	3815	3875
50 DW	3380	3435	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.