


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>420/65 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	146 D ; 151 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94058464	<b>RC (IN)</b>	137.1
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	DW 13 L ; W13
<b>OD (IN)</b>	45.6	<b>RIM ALT</b>	DW 15 L ; DW 14 L
<b>SLR (IN)</b>	20.9	<b>ECE</b>	E11-106R-005952

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
40	2650	3240	3640	4300	4890	5490	6020	6610
30	2850	3510	3920	4640	5290	5930	6500	7140
25	3040	3730	4190	4950	5630	6320	6920	7610
20	3170	3890	4360	5160	5870	6590	7220	7940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.