


# FL 695

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>600/55 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS / TRAILER   |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94072897 | <b>RC (IN)</b> | 161.0           |
| <b>SW (IN)</b>  | 23.3     | <b>RIM REC</b> | AG20.00         |
| <b>OD (IN)</b>  | 52.6     | <b>ECE</b>     | E11-106R-007937 |
| <b>SLR (IN)</b> | 24.4     |                |                 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 65    | 73    | 80    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | --   | --   | --    | 6450  | 7450  | 8450  | 9310  | 10170 | 11180 | 11890 | 12610 | 13470 | 14330 |
| 30        | --   | --   | --    | 7800  | 9020  | 10240 | 11280 | 12310 | 13520 | 14400 | 15270 | 16300 | 17340 |
| 25        | --   | 6440 | 7990  | 8770  | 10140 | 11510 | 12680 | 13840 | 15210 | 16180 | 17150 | 18320 | 19490 |
| 20        | 5410 | 7140 | 8870  | 9740  | 11250 | 12780 | 14060 | 15370 | 16890 | 17970 | 19050 | 20350 | 21640 |
| 15        | 5670 | 7470 | 9290  | 10200 | 11780 | 13360 | 14730 | 16080 | 17670 | 18790 | 19930 | 21280 | 22640 |
| 10        | 5920 | 7800 | 9700  | 10650 | 12300 | 13950 | 15380 | 16790 | 18450 | 19630 | 20810 | 22230 | 23640 |
| 5         | 6450 | 8520 | 10580 | 11610 | 13410 | 15220 | 16770 | 18320 | 20130 | 21420 | 22710 | 24250 | 25790 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.