


AGRIMAX TURF RT 333

TIRE SIZE	280/70 R 16
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	112 A8 ; 112 B



DIMENSIONER IS STANDARD

SW (MM)	289	RIM REC	W9
OD (MM)	800	RIM ALT	W 8 ; W 10
SLR (MM)	359	ECE	E11-106R-006472
RC (MM)	2371	SRI	380

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	530	605	695	785	875	965	1055	1120
40	530	605	695	785	875	965	1055	1120
30	565	650	745	840	940	1035	1130	1200
10 LT	710	815	935	1055	1175	1295	1415	1505
10 HT	565	650	745	840	940	1035	1130	1200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.