


# MULTIMAX MP 515

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>445/65 R 22.5 MPT</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | VEICOLO UNIVERSALE / AUTOCARRO<br>PER FERTILIZZANTI                                      |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 160 G  |



## DIMENSIONI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 444  | <b>RIM REC</b> | 13              |
| <b>OD (MM)</b>  | 1150 | <b>RIM ALT</b> | 14              |
| <b>SLR (MM)</b> | 527  | <b>ECE</b>     | E11-54R-0017868 |
| <b>RC (MM)</b>  | 3532 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.5  | 3.0  | 3.5  | 4.0  | 4.5  | 6.0  |
|------------|------|------|------|------|------|------|------|------|
| 90         | 1740 | 2060 | 2410 | 2750 | 3075 | 3390 | 3800 | 4500 |
| 65         | 1890 | 2235 | 2615 | 2985 | 3340 | 3675 | 4000 | 4885 |
| 40         | 2005 | 2365 | 2770 | 3165 | 3540 | 3900 | 4240 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.