

# AGRIMAX RT 955

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 270/95 R 32                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | PULVÉRISATEUR / MACHINE À<br>VENDANGER / MOISSONNEUSE /<br>OUTILLAGE AGRICOLE            |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 136 A8/B                                                                                 |



## DIMENSIONS US STANDARD

|          |          |         |                |
|----------|----------|---------|----------------|
| CODE USA | 94021857 | RC (IN) | 160.5          |
| SW (IN)  | 10.8     | RIM REC | W 9            |
| OD (IN)  | 52.2     | RIM ALT | W 8 ; W 10     |
| SLR (IN) | 24.2     | ECE     | E4-106R-000776 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64   |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30        | 1930 | 2520 | 3060 | 3360 | 3560 | 3900 | 4250 | 4600 | 4930 | -    |
| 25        | 1930 | 2520 | 3060 | 3360 | 3560 | 3900 | 4250 | 4600 | 4930 | -    |
| 20        | 2070 | 2700 | 3280 | 3600 | 3810 | 4190 | 4550 | 4930 | 5290 | -    |
| 5         | 2300 | 2900 | 3560 | 4230 | 4890 | 5040 | 5630 | 6230 | 6820 | 7410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.