


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/95 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	181 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	2182	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	991	<b>ECE</b>	E11-106R-0010083
<b>RC (MM)</b>	6606	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
<b>70</b>	4045	4500	5035	5495	5800	6025	6255	6485	6790	7095	7325	7630
<b>FROM 65 TO 40</b>	4375	4865	5445	5940	6270	6515	6765	7015	7345	7675	7920	8250
<b>30</b>	4460	4960	5550	6060	6400	6645	6900	7155	7490	7825	8080	8415
<b>20</b>	4550	5060	5660	6180	6525	6775	7035	7295	7635	7980	8240	8580
<b>10</b>	4810	5350	5985	6535	6900	7165	7440	7715	8075	8440	8715	9075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.