

# ROCK GRIP E4

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | 16.00 - 25       |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK |
| <b>VERSION</b>      | STEEL BELTED     |
| <b>TIRE TYPE</b>    | TL               |



## DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA CODE</b> | 94059621 | <b>RIM REC</b>  | 11.25/2.0 |
| <b>OD (IN)</b>  | 60.0     | <b>RIM ALT</b>  | 13.00/2.0 |
| <b>SLR (IN)</b> | 27.5     | <b>PR</b>       | 32        |
| <b>RC (IN)</b>  | 177.7    | <b>TRA CODE</b> | E4        |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>127</b> |
| 5                | 27600      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.