

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>240/60 R 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / MAQUINA PARA RECOLHA DOS FRUTOS / TRATOR PEQUENO / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	89



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	242	<b>RIM REC</b>	7
<b>OD (MM)</b>	592	<b>ECE</b>	E11-106R-007679
<b>SLR (MM)</b>	269		
<b>RC (MM)</b>	1777		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	270	310	355	395	445	485	540	580
40	270	310	355	395	445	485	540	580
30	290	335	385	425	475	520	585	625
10 LT	360	415	480	535	595	650	730	780
10 HT	290	335	385	425	475	520	585	625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.