


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>850/50 R 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPREADER / TANKER / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	860	<b>RIM REC</b>	AG 28.00
<b>OD (MM)</b>	1625	<b>ECE</b>	E11-106R-008232
<b>SLR (MM)</b>	722	<b>SRI</b>	775
<b>RC (MM)</b>	4895		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	3175	3945	4490	5185	5880	6425	7040	7735
65	3485	4335	4930	5695	6460	7055	7735	8500
50	4220	5250	5970	6895	7820	8540	9360	10285
40	4740	5900	6705	7750	8790	9595	10520	11560
25	5510	6850	7790	9000	10210	11150	12225	13430
10	6275	7805	8875	10255	11630	12700	13925	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.