

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>280/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	116 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	275	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	900	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (MM)</b>	408	<b>ECE</b>	E4-106R-00641
<b>RC (MM)</b>	2705	<b>SRI</b>	450

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>50</b>	590	675	775	875	975	1075	1165	1250
<b>40</b>	590	675	775	875	975	1075	1165	1250
<b>30</b>	630	725	835	940	1050	1155	1250	1340
<b>10 LT</b>	790	905	1040	1175	1310	1445	1560	1675
<b>10 HT</b>	630	725	835	940	1050	1155	1250	1340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.