

# AGRIMAX V- FLECTO

**VF 650/60 R 38**

|              |  |
|--------------|--|
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR   |
| VERSION      | STANDARD   |
| TIRE TYPE    | TL   |
|              | 166 D  |



## UNDEFINED IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 650  | RIM REC | DW 23 B         |
| OD (MM)  | 1745 | RIM ALT | DW 21 B         |
| SLR (MM) | 774  | ECE     | E11-106R-005712 |
| RC (MM)  | 5231 | SRI     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------------------------|------|------|------|------|------|------|
| 70                             | 2650 | 3080 | 3515 | 3950 | 4385 | 4820 |
| FROM 65 TO 40                  | 2915 | 3390 | 3865 | 4345 | 4820 | 5300 |
| 30                             | 2970 | 3455 | 3940 | 4430 | 4915 | 5405 |
| 20                             | 3030 | 3525 | 4015 | 4515 | 5010 | 5510 |
| 10                             | 3205 | 3725 | 4250 | 4775 | 5300 | 5830 |
| *UPTO 10 CYC WITH FRONT LOADER | 4080 | 4745 | 5410 | 6080 | 6745 | 7420 |
| 10HT                           | 2970 | 3455 | 3940 | 4430 | 4915 | 5405 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.